



Load Capacity of Systems

2010

Single Point Systems	Wood Panel
Ipuc 10 (varies upon accessory arm selected)	10kg or 22 lbs
Ipuc 25 (varies upon accessory arm selected)	25kg or 55lbs
Spot 12 (varies upon accessory arm selected)	10kg or 22 lbs
Spot 25 (varies upon accessory arm selected)	25kg or 55lbs
Slotted Panel (3" length x 6" vertical spacing)	5kg or 11lbs

Horizontal Systems	
Slatwall 3"o/c 2000 / 5000 series (single point load 6" off panel face)	15kg or 30lbs
Slatwall 3"o/c 7000 series (single point load 6" off panel face)	35kg or 75lbs
Slatwall 6"o/c Insert 101 (Temp glass shelf 24x10x.25)	8kg or 17lbs

Vertical Systems	
Fixo (varies upon accessory arm selected)	2kg - 40 kg or 4lbs - 88lbs
Global (varies upon accessory arm selected)	2kg - 40 kg or 4lbs - 88lbs

Floor Fixture Systems	
Xpuc	10kg or 22 lbs
Slatwall	See Horizontal

These are recommended maximum loads per holder. Your results may vary depending on the accessory arm selected, load positioning, substrate material and attachment method, etc. To verify your specific requirements you need to test accordingly. Marlite is not liable for your actual results or failures.