

# Induro™ HPL-Faced FRP





Tough surface prevents wall damage.



Eliminates the need for spot repairs.



The easiest, most affordable way to apply HPL to walls.

# Stands up. To just about anything.

Wall protection for high traffic areas.

## What is HPL-Faced FRP?

The ultimate in wall protection, High Pressure Laminate (HPL)-faced FRP is an exceptionally wear resistant panel. It is created through an exclusive process of thermally bonding melamine impregnated surfacing materials directly to the FRP core. Designed to match and coordinate with popular high pressure laminates, the panels are available in a wide array of woodgrains, solid colors and abstract prints.

#### Scratch Resistant Test ASTM D2197



Competitive Rigid Plastic Wall Panel



HPL-faced FRP Panel

#### Impact Test ASTM D5420-04 product on 1/2" drywall





Rigid plastic wall panel Complete structural failure

HPL-faced FRP wall panel nominal damage

## **Panel Information**

### **Panel Sizes**

Panel Dimension - 47.5" x 95.5" x 3/32" (nominal)

Class A and Class C fire-ratings.

Material conforms with NFPA Life Safety Code Class A fire rating.

### HPL-Faced FRP vs. Painted Drywall





# When durability is essential.

## **Finish Options**

### **Faux Woodgrains**



7925 Monticello Maple



7061 Natural Pear



FP610 Hard Rock Maple



7922 **Brighton Walnut** 



7924 Biltmore Cherry



7939 Blonde Echo



Pewter Mesh

### **Abstract Patterns**



4143 Neutral Glace



4746



FP612 Woolamai Brush Graphite Spectrum



4810 Titanium



4745 Maroochy Brush

### **Solid Colors**



D354 Designer White

D381

Fashion Grey

HPL-faced FRP can be special ordered in laminate finishes from these manufacturers.









# **Trim Options**

#### Harmonizing Aluminum Trim

Durable painted Aluminum Trim Moldings harmonize with any FRP finish.







Inside Corner Outside Corner A560 A551

**Anodized Aluminum Trim** 

for use with any FRP finish.



Division A565

Satin, Bright Satin, or Black Satin Anodized Aluminum Trim Moldings



A570

## Hand Rails & Corner Guards



mX7 Series Flat Hand Rail



mX8 Series Accent Strip





F551

Installation

Using suggested

edge.

for 100% coverage

within 2" from each

trowel, spread adhesive

Outside Corner F560



Division F565



F570





Press & roll from center over entire

Use only approved adhesives and sealants.



Apply a 1/4" thick bead of Marlite C-109 Flex panel to fit in trim Cartridge Adhesive 3/4" in from edges and cutouts.

Marlite









www.marlite.com 800.377.1221

LIT-FRP-202102 Effective date: 11/30/21 Copyright 2021