

3A Composites

Safety Data Sheet

Veneer® Initial Release Date: May 2004

Revision Date: January 7, 2015

Section I	Product Identification
Manufacturer:	3A Composites USA, Inc. 3480 Taylorsville Highway Statesville, NC 28687-1839 (800) 872-8974
Emergency Phone Number:	1-800-424-9300 Chemtrec To be used only in the event of chemical emergencies involving a spill, leak, fire, and exposure accidents involving chemicals.
Trade Name:	Veneer®
Synonym:	Luxcell® faces; Gator-Ply® backs; Syn-Ply™ cross band.

Section II	Hazard Identification
<p>This product contains condensed urea-formaldehyde based polymeric resin, which is classified as a non-hazardous component when polymerized.</p> <p>Formaldehyde is listed by the International Agency for Research on Cancer (IARC) as a carcinogen for which there is limited evidence of carcinogenicity in humans. The National Toxicology Program (NTP) includes formaldehyde in the annual report on carcinogens. OSHA considers formaldehyde as a carcinogen.</p>	

Section III			Chemical Composition		
Ingredients (Common Name)		CAS Number		Percent (%) by Weight	
Formaldehyde		50-00-0		<0.01	

Section IV	First Aid Measures
Emergency and first aid procedures:	For dust contact with eyes, wash immediately under water for at least 15 minutes For dust inhalation exposure, remove to fresh air. Contact a physician.

Section V	Fire Fighting Measures
Extinguishing media:	Water, foam, CO ₂ , dry chemical powder

3A Composites

Safety Data Sheet

Veneer® Initial Release Date: May 2004

Revision Date: January 7, 2015

Special firefighting procedure: Toxic gases may form upon combustion.
Respiratory protection is recommended.

Thermal decomposition: May release hazardous or toxic gases

Section VI Accidental Release

IN CASE MATERIAL IS SPILLED OR RELEASED:

Do not use compressed air to remove dust. Vacuum or wet mop area.

Section VII Handling and Storage

Store in a well-ventilated area. Allow shipping vehicles to ventilate before unloading. Vents should be kept open on vehicles during transit. Materials should not be stored in a confined unventilated area.

Section VIII Exposure Controls

Nuisance dust may be generated during cutting or abrading operations. OSHA considers nuisance dust as Particulate Not Otherwise Regulated (PNOR) with an OSHA PEL of 15 mg/m³ (total dust) and 5 mg/m³ (respirable dust). ACGIH considers nuisance dust as Particulates Not Otherwise Classified (PNOC) with an ACGIH TLV of 10 mg/m³ (inhalable particulate) and 3 mg/m³ (respirable particulate).

Section IX Physical and Chemical Properties

Appearance:	Rigid, resin impregnated, colored paper product.
Odor:	NA
Odor Threshold:	NA
PH:	NA
Melting Point:	NA
Initial Boiling Point/Boiling Range:	NA
Flash Point:	NA
Evaporation Rate:	NA
Flammability:	NA
Upper/lower explosive limit:	NA
Vapor Pressure:	NA
Vapor Density:	NA
Specific Gravity:	NA
Solubility:	NA
Partition coefficient:	NA
Auto-Ignition:	NA
Decomposition Temperature:	NA
Viscosity:	NA

3A Composites

Safety Data Sheet

Veneer® Initial Release Date: May 2004

Revision Date: January 7, 2015

Section X	Stability and Reactivity
-----------	--------------------------

Stability:	Heat and moisture can result in increased rates of off gassing of formaldehyde
Incompatibility:	None known
Decomposition products:	None known
Conditions to avoid:	Open flame. High temperatures

Section XI	Toxicology Information
------------	------------------------

No information available at this time

Section XII	Ecological Information
-------------	------------------------

No information available at this time

Section XIII	Disposal Information
--------------	----------------------

Waste disposal:	Care must be taken when using or disposing of material debris to prevent environmental contamination. Dispose of the debris in accordance with the Clean Air Act, the Clean Water Act, the Resource Conservation and Recovery Act and all state or local laws / regulations regarding disposal.
-----------------	---

Section XIV	Transportation
-------------	----------------

UN Number: NA
UN Proper Shipping Name: NA
Transportation Hazard: NA
Packing Group: NA
Environmental Hazard: NA
Transport in bulk: NA
Special Precautions: NA

3A Composites

Safety Data Sheet

Veneer® Initial Release Date: May 2004

Revision Date: January 7, 2015

Section XV	Regulatory Information
------------	------------------------

REACH: Pursuant to Title II article 7 of the regulation this product is exempt from registration and notification and is therefore compliant with the REACH regulation.

RoHS: The Gatorfoam® and Fome-Cor® family of products are compliant with the ROHS standard.

Section XVI	Other Information
-------------	-------------------

Abbreviations:

NA = Not Applicable CAS = Chemical Abstract Service

OSHA = Occupational Safety and Health Administration. PEL = Permissible Exposure Limit

STEL = Short Term Exposure Limit. ACGIH = American Conference of Governmental Industrial Hygienist. TLV = Threshold Limit Value.

IMPORTANT: The information and data contained herein are believed to be accurate and have been compiled from sources believed to be accurate. All information contained herein is offered for your consideration, information, investigation, and verification. 3A COMPOSITES MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DATA HEREIN. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY EXCLUDED. 3A Composites will not be responsible for claims relating to any parties' use of or reliance on information and data contained herein regardless of whether it is claimed that the information are inaccurate, incomplete, or otherwise misleading

End of Safety Data Sheet