marlite®
your world on a wall

# Standard FRP
## Smooth & Pebbled




**The most trusted name in FRP wall panels.**

# Standard FRP

Marlite Standard FRP delivers proven performance in durability and quality. As the most specified of fiberglass reinforced plastic (FRP), we know the importance of maintaining sanitary conditions in high-traffic areas, ensuring code compliance, and protecting walls, even in moisture-prone environments.

- .090-inch thickness for durability and impact resistance
- USDA/FSIS/CFIA-approved for food-safe environments
- Fast, straightforward installation to reduce labor costs
- Easy-to-clean surface that stands up cleaning protocols
- Class A and Class C fire ratings to meet building codes
- Smooth or pebbled textures available in 4′ x 8′, 4′ x 9′, and 4′ x 10′ panels



## Features & Benefits



**Stain Resistant**



**Impact Resistant**



**Water Resistant**



**Scratch Resistant**



**Fire Rated**

## Panel Information

**Panel Specifications:** (Nominal Panel Sizes)

**Class C Fire-Rated:**

4’ x 8’
4’ x 9’ (select finishes)
4’ x 10’
4’ x 12’ (P 100 White)

**Class A Fire-Rated:**

4’ x 8’
4’ x 9’ (P 100 White)
4’ x 10’

**Panel Thickness:**

3/32” or .090”

GREENGUARD Certified

FM Approved

Meets USDA/FSIS/CFIA requirements

## FRP Ceiling Panels

**FRP P100CP White**

2’ x 4’ x 3/32” (Class C)
2’ x 4’ x 3/32” (Class A, C)

**FRP P100CP with Gypsum**

2’ x 4’ x 23/32” (Class A)

.090 FRP laminated to 5/8” fire-rated Gypsum

# Pebbled FRP


**P 100 White**


**P 199 Bright White**


**P 118 Natural Almond**


**P 145 Silver**


**P 106 Beige**


**P 140 Ivory**


**P 440N Biscuit**


**P 151 Light Grey**


**P 430N Medium Grey**


**P 470N Dark Grey**


**P 807 Black**

Standard FRP is available in Class A and Class C. Lead times and minimums may apply.

# Smooth FRP


**S 100 S/2/S White**


**S 100G White**


**S 118G Almond**


**S 490N Light Grey**


**S 807N Black**

# Trim Options

Available in Anodized Aluminum and PVC.


**Inside Corner** A551


**Outside Corner** A560


**Division** A565


**Edge** A570


**Inside Corner** M350


**Outside Corner** M360


**Division** M365


**Edge** M370


**135° Inside Corner** V177


**135° Outside Corner** V179


**PVC Base Molding 4" x 10'** M612


**Butt Joint Connector**
Included with Base Molding Strips


**End Caps** M625 RH/M620 LH


**Outside Corner** M660


**Inside Corner** M651


**3" Base Cove** V65


**Stainless Corner Guard** F56OSS


**PVC Outside Corner Guard** M961

# Installation



Measure and cut FRP panels to size using a table saw.



Apply Marlite FRP adhesive evenly to panel back.



Position and adhere panel to prepared subwall.



For seam joints, install division molding under first panel edge.



Secure molding with staples along pre-sealed edge.



Place second panel against molding and repeat.

## Adhesive Options

**C551**




For use with FRP panels over porous subwalls such as unfinished drywall and plywood.

**Advanced Polymer**




For use with FRP panels over non-porous surfaces such as ceramic tile and moisture resistant drywall.

**Silicone Sealant**



For use with FRP moldings. MS-250 Clear, MS-251 White, and Color Matched

marlite
your world on a wall

Follow us on:

VISUAL WALL PANELS

www.marlite.com
800.377.1221

1 Marlite Drive
Dover, Ohio 44622

LIT-FRP-202002
Effective 11/19/26
Copyright 2026